MOLYDUVAL Soraja CL Spray









Food Grade Cleaner Spray

A relative environmentally friendly cleaner for maintenance, repair, and assembly, for degreasing parts and tools in Food industry. Removes grease, grit and grime from most

It can be supplied to meet the requirements of the US Food and Drug Adminstration (FDA) specifications published in the code of Federal Regulations Chapter 21, Subchapter B, Parts

172.882 Synthetic isoparaffinic petroleum hydrocarbons. In the froth-flotation cleaning of vegetables

178.3530 Isoparaffinic Solvents

172.884 Odorless Light Petroleum Hydrocarbons For Cleaning in Direct Food Contact Applications

178.3620 Technical White Mineral Oil

178.3650 Odorless Light Petroleum Hydrocarbons

and the medical use requirements of the German DAB 10.

Users should make their own assessment of compliance with the relevant regulation.

characteristics

- * biodegradable
- * clear color
- * low odor
- very economic * odor less

Applications

- * for cleaning and degreasing
- * for cleaning engines, motors, steerings * for cleaning tools and machines
- * for cleaning inox containers and machines
- * for floor cleaning
- * for cleaning and flushing of machines in food industry
- * for die cleaning

Specifications

The product can be supplied that the active agent in the aerosol can meets the requirements of the US Food and Drug Adminstration (FDA) specifications published in the code of Federal Regulations Chapter 21, Subchapter B,

PART 172 FOOD ADDITIVES PERMITTED FOR DIRECT ADDITION TO FOOD FOR HUMAN CONSUMPTION

172.882 Synthetic isoparaffinic petroleum hydrocarbons

172.884 Odorless light petroleum hydrocarbons.

PART 178 INDIRECT FOOD ADDITIVES: ADJUVANTS, PRODUCTION AIDS, AND SANITIZERS

178.3530 Isoparaffinic petroleum hydrocarbons, synthetic

178.3620 Mineral oil

178.3650 Odorless light petroleum hydrocarbons

and the medical use requirements of the German DAB10. Users of it should make their

For further information, please see our website www.molyduval.com or consult your local representative.

MOLYDUVAL Soraja CL Spray

own assessment of compliance with the relevant regulation.

Technical Datas			
Color		transparent	
Base Fluid		HC	
Viscosity 25°C	mm²/s	1,6	
Density 40°C	kg/m³	750	
Flash Point COC	°C	44	